


**Becker's A Fiksative
338440**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** Becker's A Fiksative
338440
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Fixative
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:** A. Wennström Oy /Porvoon teknillinen tehdas
Värjärintie 3-5
16230 Artjärvi
p. +358 3882 590
fax. +358 3882 5959

VAT 04201846
- 1.4 Emergency telephone number:** Yleinen hätänumero:112 Myrkytystietokeskus, PL 790
(Tukholmankatu 17), 00029 HUS:09-471977

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
Directive 67/548/EC and Directive 1999/45/EC:
This product was classified in accordance with Directive 67/548/EC and Directive 1999/45/EC, adapting the requirements to Regulation (EC) n°1907/2006 (REACH regulation).
F+: R12 - Extremely flammable
CLP Regulation (EC) n° 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) n° 1272/2008.
Aerosol 1: Pressurised container: May burst if heated.
Aerosol 1: Flammable aerosols, Category 1
Eye Irrit. 2: Eye irritation, Category 2
- 2.2 Label elements:**
CLP Regulation (EC) n° 1272/2008:
Danger

Hazard statements:
Aerosol 1: H229 - Pressurised container: May burst if heated
Aerosol 1: H222 - Extremely flammable aerosol
Eye Irrit. 2: H319 - Causes serious eye irritation
Precautionary statements:
P101: If medical advice is needed, have product container or label at hand
P102: Keep out of reach of children
P103: Read label before use
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P251: Do not pierce or burn, even after use
P280: Wear protective gloves/protective clothing/eye protection/face protection
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
Supplementary information:
Non-applicable
- 2.3 Other hazards:**
Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical description: Aerosol





- CONTINUED ON NEXT PAGE -

**Becker's A Fiksative
338440**

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continue)

Components:

In accordance with Annex II of Regulation (EC) n°1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 64-17-5 EC: 200-578-6 Index: 603-002-00-5 REACH: 01-2119457610-43-XXXX	Ethanol Self-classified		 50 - <75 %
	Directive 67/548/EC	F: R11	
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225 - Danger	
CAS: 106-97-8 EC: 203-448-7 Index: 601-004-00-0 REACH: 01-2119474691-32-XXXX	Butane ATP CLP00		 25 - <50 %
	Directive 67/548/EC	F+: R12	
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	
CAS: 74-98-6 EC: 200-827-9 Index: 601-003-00-5 REACH: 01-2119486944-21-XXXX	Propane ATP CLP00		 2,5 - <10 %
	Directive 67/548/EC	F+: R12	
	Regulation 1272/2008	Flam. Gas 1: H220; Press. Gas: H280 - Danger	
CAS: 78-83-1 EC: 201-148-0 Index: 603-108-00-1 REACH: 01-2119484609-23-XXXX	Isobutanol ATP CLP00		 1 - <2,5 %
	Directive 67/548/EC	Xi: R37/38, R41; R10; R67	
	Regulation 1272/2008	Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335; STOT SE 3: H336 - Danger	

To obtain more information on the risk of the substances consult sections 8, 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the MSDS of this product.

By inhalation:

This product is not classified as dangerous through inhalation, however, it is recommended in case of intoxication symptoms to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as dangerous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or shower the person affected if necessary thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with luke warm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the MSDS of the product.

By consumption:

Do not induce vomiting, but if it does happen keep the head up to avoid inhalation. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use tap water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

Contains substances that may result in explosion caused by heat. In case of fire follow the instructions on the Internal Emergency Plan.

5.3 Advice for firefighters:

- CONTINUED ON NEXT PAGE -

Becker's A Fiksative
338440

SECTION 5: FIREFIGHTING MEASURES (continue)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inertizing agent. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions:

This product is not classified as dangerous to the environment. Keep product away from drains, surface and underground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 94/9/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

- CONTINUED ON NEXT PAGE -

**Becker's A Fiksative
338440**

SECTION 7: HANDLING AND STORAGE (continue)

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the work environment

There are no environmental limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable
	Inhalation	Non-applicable	1900 mg/m ³	950 mg/m ³	Non-applicable
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	310 mg/m ³

DNEL (Population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Ethanol CAS: 64-17-5 EC: 200-578-6	Oral	Non-applicable	Non-applicable	87 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	206 mg/kg	Non-applicable
	Inhalation	Non-applicable	950 mg/m ³	114 mg/m ³	Non-applicable
Isobutanol CAS: 78-83-1 EC: 201-148-0	Oral	Non-applicable	Non-applicable	25 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	55 mg/m ³

PNEC:

Identification					
Ethanol CAS: 64-17-5 EC: 200-578-6	STP	580 mg/L	Fresh water	0,96 mg/L	
	Soil	Non-applicable	Marine water	0,79 mg/L	
	Intermittent	2,75 mg/L	Sediment (Fresh water)	3,6 mg/kg	
	Oral	720 g/kg	Sediment (Marine water)	Non-applicable	
Isobutanol CAS: 78-83-1 EC: 201-148-0	STP	10 mg/L	Fresh water	0,4 mg/L	
	Soil	0,0699 mg/kg	Marine water	0,04 mg/L	
	Intermittent	11 mg/L	Sediment (Fresh water)	1,52 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,152 mg/kg	



8.2 Exposure controls:

A.- General security and hygiene measures in the work place

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the professional exposure limits. In case of using individual protection equipment they should have the ""CE marking"" in accordance with Directive 89/686/EC. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Compulsory use of face mask	Filter mask for particles		EN 149:2001+A1:2009	Replace when an increase in resistance to breathing is observed.

C.- Specific protection for the hands



- CONTINUED ON NEXT PAGE -

**Becker's A Fiksative
338440**





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continue)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves		EN 374-1:2003 EN 374-3:2003/AC:2006 EN 420:2003+A1:2009	Replace the gloves at any sign of deterioration.



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against liquid splash		EN 166:2001 EN 172:1994/A1:2000 EN 172:1994/A2:2001 EN ISO 4007:2012	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Antistatic and fireproof protective clothing		EN 1149-1:2006 EN 1149-2:1997 EN 1149-3:2004 EN 168:2001 EN ISO 14116:2008/AC:2009 EN 1149-5:2008	Limited protection against flames.
 Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		EN 13287:2008 EN ISO 20345:2011 EN ISO 20344:2011	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2002	 Eyewash stations	DIN 12 899 ISO 3864-1:2002

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatil organic compounds:

With regard to Directive 1999/13/EC, this product has the following characteristics:

V.O.C. (Supply):	100 % weight
V.O.C. density at 20 °C:	Non-applicable
Average carbon number:	2,04
Average molecular weight:	46,66 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Fluid
Color:	Colourless
Odor:	Mild

Volatility:

Boiling point at atmospheric pressure:	-42 °C (Propellant)
--	---------------------

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Becker's A Fiksative
338440

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continue)

Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	811 kg/m³ 20 °C (etanol)
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility property:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Recipient pressure:	Non-applicable *

Flammability:

Flash Point:	-104 °C (Propellant)
Autoignition temperature:	410 °C (Propellant)
Lower flammability limit:	1,9 vol%
Upper flammability limit:	8,5 vol%

9.2 Other information:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected if the following technical instructions storage of chemicals. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Combustive materials	Combustible materials	Others
Not applicable	Not applicable	Avoid direct impact	Avoid direct impact	Not applicable

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

- CONTINUED ON NEXT PAGE -

Becker's A Fiksative
338440

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

No experimental information is available on the product itself in relation to the toxicological properties. When performing the danger classification on corrosive or irritant effects the recommendations included in section 3.2.5 of Annex VI of Directive 67/548/EC, in paragraphs b) and c) of section 3 of article 6 of Directive 1999/45/EC and in section 3.2.3.3.5. of Annex I of CLP Regulation were taken into account.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A.- Ingestion:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.

B- Inhalation:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

C- Contact with the skin and the eyes:

Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

E- Sensitizing effects:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitizing effects. For more information see section 3.

F- Specific target organ toxicity (STOT)-time exposure:

Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Ethanol CAS: 64-17-5 EC: 200-578-6	LD50 oral	6200 mg/kg	Rat
	LD50 dermal	20000 mg/kg	Rabbit
	LC50 inhalation	124,7 mg/L (4 h)	Rat
Isobutanol CAS: 78-83-1 EC: 201-148-0	LD50 oral	3350 mg/kg	Rat
	LD50 dermal	2460 mg/kg	Rabbit
	LC50 inhalation	24,6 mg/L (4 h)	Rat
Butane CAS: 106-97-8 EC: 203-448-7	LD50 oral	Non-applicable	
	LD50 dermal	Non-applicable	
	LC50 inhalation	658 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the ecotoxicological properties of the product itself is not available

12.1 Toxicity:

Identification	Acute toxicity		Specie	Genus
Ethanol CAS: 64-17-5 EC: 200-578-6	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Alga

- CONTINUED ON NEXT PAGE -

**Becker's A Fiksative
338440**

SECTION 12: ECOLOGICAL INFORMATION (continue)

Identification	Acute toxicity		Specie	Genus
Isobutanol	LC50	2030 mg/L (96 h)	Carassius auratus	Fish
CAS: 78-83-1	EC50	1439 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-148-0	EC50	1250 mg/L (48 h)	Scenedesmus subspicatus	Alga

12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
Ethanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64-17-5	COD	Non-applicable	Period	14 days
EC: 200-578-6	BOD5/COD	0.57	% Biodegradable	89 %
Isobutanol	BOD5	0.4 g O2/g	Concentration	100 mg/L
CAS: 78-83-1	COD	2.41 g O2/g	Period	14 days
EC: 201-148-0	BOD5/COD	0.17	% Biodegradable	90 %

12.3 Bioaccumulative potential:

Identification	Bioaccumulation potential	
Ethanol	BCF	3
CAS: 64-17-5	Pow Log	-0,31
EC: 200-578-6	Potential	Low
Butane	BCF	33
CAS: 106-97-8	Pow Log	2,89
EC: 203-448-7	Potential	Moderate
Propane	BCF	13
CAS: 74-98-6	Pow Log	2,86
EC: 200-827-9	Potential	Low
Isobutanol	BCF	3
CAS: 78-83-1	Pow Log	0,76
EC: 201-148-0	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Ethanol	Koc	1	Henry	4,61E-1 Pa·m ³ /mol
CAS: 64-17-5	Conclusion	Very High	Dry soil	Yes
EC: 200-578-6	Surface tension	23390 N/m (25 °C)	Moist soil	Yes
Butane	Koc	900	Henry	9,626E+4 Pa·m ³ /mol
CAS: 106-97-8	Conclusion	Low	Dry soil	Yes
EC: 203-448-7	Surface tension	11870 N/m (25 °C)	Moist soil	Yes
Propane	Koc	460	Henry	7,164E+4 Pa·m ³ /mol
CAS: 74-98-6	Conclusion	Moderate	Dry soil	Yes
EC: 200-827-9	Surface tension	7020 N/m (25 °C)	Moist soil	Yes
Isobutanol	Koc	Non-applicable	Henry	Non-applicable
CAS: 78-83-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-148-0	Surface tension	23780 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Directive 2008/98/EC)
16 05 04*	Gases in pressure containers (including halons) containing dangerous substances	Dangerous

Waste management (disposal and evaluation):

- CONTINUED ON NEXT PAGE -

**Becker's A Fiksative
338440**

SECTION 13: DISPOSAL CONSIDERATIONS (continue)

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2000/532/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) n°1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2000/532/EC: Commission Decision of 3 May 2000

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2013 and RID 2013:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Dangerous for the environment: | No |
| 14.6 Special precautions for user | |
| Special regulations: | 190, 327, 625 |
| Tunnel restriction code: | D |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: | Non-applicable |

Transport of dangerous goods by sea:

With regard to IMDG 36-12:



- | | |
|---|---------------------|
| 14.1 UN number: | UN1950 |
| 14.2 UN proper shipping name: | AEROSOLS, flammable |
| 14.3 Transport hazard class(es): | 2 |
| Labels: | 2.1 |
| 14.4 Packing group: | N/A |
| 14.5 Dangerous for the environment: | No |
| 14.6 Special precautions for user | |
| Special regulations: | Non-applicable |
| EmS Codes: | F-D, S-U |
| Physico-Chemical properties: | see section 9 |
| Limited quantities: | 1 L |
| 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: | Non-applicable |

Transport of dangerous goods by air:

With regard to IATA/ICAO 2014:

**Becker's A Fiksative
338440**

SECTION 14: TRANSPORT INFORMATION (continue)



- 14.1 UN number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
Labels: 2.1
14.4 Packing group: N/A
14.5 Dangerous for the environment: No
14.6 Special precautions for user
Physico-Chemical properties: see section 9
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) 1907/2006 (REACH): Non-applicable
Regulation (EC) 1005/2009, about substances that deplete the ozone layer: Non-applicable
Active substances for which a decision of non-inclusion onto Annex I (Regulation (EU) No 528/2012): Non-applicable
Regulation (EC) 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII, REACH):

Non-applicable

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Other legislation:

Non-applicable

Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers
Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers
Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers
Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) N° 1907/2006 (Regulation (EC) N° 453/2010)

Modifications related to the previous security card which concerns the ways of managing risks. :

Non-applicable

Text of R-phrases considered in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

Directive 67/548/EC and Directive 1999/45/EC:

**Becker's A Fiksative
338440**

SECTION 16: OTHER INFORMATION (continue)

R10: Flammable
R11: Highly flammable
R12: Extremely flammable
R37/38: Irritating to respiratory system and skin
R41: Risk of serious damage to eyes
R67: Vapours may cause drowsiness and dizziness

CLP Regulation (EC) n° 1272/2008:

Eye Dam. 1: H318 - Causes serious eye damage
Eye Irrit. 2: H319 - Causes serious eye irritation
Flam. Gas 1: H220 - Extremely flammable gas
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Flam. Liq. 3: H226 - Flammable liquid and vapour
Press. Gas: H280 - Contains gas under pressure, may explode if heated
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H335 - May cause respiratory irritation
STOT SE 3: H336 - May cause drowsiness or dizziness

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://esis.jrc.ec.europa.eu>
<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

- ADR: European agreement concerning the international carriage of dangerous goods by road
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol–water partition coefficient
- Koc: Partition coefficient of organic carbon

The information contained in this security data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this security data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -