



Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 1

PP GASKET 70 ML

SDS no. : 217185
V001.0

Revision: 10.03.2009
printing date: 26.03.2009

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

PP GASKET 70 ML

Intended use:

Sealant

Company name:

Henkel Norden AB
Box 8823
402 71 Göteborg

Sweden

Phone: +46 (31) 750 5400

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 (0)20 8312 0291

2. Hazards identification

The product is not hazardous within the meaning of the valid (EU) preparation directive.

3. Composition / information on ingredients

General chemical description:

Acetoxy curing silicone

Declaration of ingredients according to (EC) No 1907/2006:

Hazardous components CAS-No.	EINECS ELINCS	content	Classification
Triacetoxyethylsilane 17689-77-9	241-677-4	1 - 5 %	C - Corrosive; R34 Xn - Harmful; R22 R14
Methyltriacetoxyethylsilane 4253-34-3	224-221-9	1 - 5 %	R14 C - Corrosive; R34 Xn - Harmful; R22

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

Acetic acid is liberated slowly upon contact with moisture.

4. First aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.
Seek medical advice.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse out mouth, drink 1-2 glasses of water, do not induce vomiting.
Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

Carbon dioxide, foam, powder

Special protection equipment for firefighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

6. Accidental release measures

Personal precautions:

Avoid skin and eye contact.

Environmental precautions:

Do not let product enter drains.

Clean-up methods:

For small spills wipe up with paper towel and place in container for disposal.
For large spills absorb onto inert absorbent material and place in sealed container for disposal.

7. Handling and storage

Handling:

Use only in well-ventilated areas.
Avoid skin and eye contact.
Prolonged or repeated skin contact should be avoided to minimise any risk of sensitisation.

Storage:

Store in original containers at 8-21C (46.4-69.8F) and do not return residual materials to containers as contamination may reduce the shelf life of the bulk product.

8. Exposure controls / personal protection

Respiratory protection:

Use only in well-ventilated areas.

Hand protection:

The use of chemical resistant gloves such as Nitrile are recommended.
Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Wear protective glasses.

Skin protection:

Wear suitable protective clothing.

General protection and hygiene measures:

Good industrial hygiene practices should be observed.

9. Physical and chemical properties

General characteristics:

Appearance	Paste
	Red
Odor:	Vinegar

Phys./chem. properties:

Flash point	> 150 °C (> 302 °F)
Solubility (qualitative) (Solvent: Water)	Insoluble

10. Stability and reactivity

Conditions to avoid:

Stable under normal conditions of storage and use.

11. Toxicological information

Oral toxicity:

May cause irritation to the digestive tract.

Inhalative toxicity:

Acetic acid is liberated slowly upon contact with moisture.
Inhalation of vapors in high concentration may cause irritation of respiratory system

Skin irritation:

Prolonged or repeated contact may cause skin irritation.

Eye irritation:

Acetic acid released during polymerisation of acetoxy curing RTV silicones is irritating to the eyes

12. Ecological information

Mobility:

Cured adhesives are immobile.

General ecological information:

Do not empty into drains / surface water / ground water.
Cured Loctite products are typical polymers and do not pose any immediate environmental hazards.

13. Disposal considerations

Product disposal:

Dispose of in accordance with local and national regulations.
Contribution of this product to waste is very insignificant in comparison to article in which it is used

Waste code():

08 04 09 waste adhesives and sealants containing organic solvents and other dangerous substances

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Disposal must be made according to official regulations.

14. Transport information

General information:

Not hazardous according to RID, ADR, ADNR, IMDG, IATA-DGR.

15. Regulations - classification and identification

Risk phrases:

Not classified as hazardous.

16. Other information

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicated by codes in this safety data sheet are as follows:

R14 Reacts violently with water.

R22 Harmful if swallowed.

R34 Causes burns.

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

This safety data sheet was prepared in accordance with Council Directive 67/548/EEC and its subsequent amendments, and Commission Directive 1999/45/EC.