

Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 5

SDS no.: 315307

V001.0 Revision: 06.06.2008

printing date: 04.05.2010

1. Identification of the substance/preparation and of the company/undertaking

Trade name:

UniBond Anti Mould Grout Reviver for Floors & Walls White

UniBond Anti Mould Grout Reviver for Floors & Walls White

Intended use:

Joint colour

Intended use:

Joint colour

Company name:

Henkel Limited Apollo Court, 2 Bishop Square Business Park Hatfield, Hertfordshire AL10 9EY

Great Britain

Phone: +44 (0)1606 593933 Fax-no.: +44 (0)1606 863762

E-mail address of person responsible for Safety Data Sheet:

ua-productsafety.uk@uk.henkel.com

Emergency information:

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

2. Hazards identification

The product is not hazardous within the meaning of the valid (EU) preparation guideline.

3. Composition / information on ingredients

General chemical description:

Coatings

Base substances of preparation:

Mineral fillers

Contains no dangerous substances exeeding the limits of the EU-Directive

4. First aid measures

General information:

In case of adverse health effects seek medical advice.

MSDS-No.: 315307 V001.0

Inhalation:

Move to fresh air.

Skin contact:

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

Eye contact:

Rinse immediately with plenty of running water, seek medical advice if necessary.

Ingestion:

Rinse mouth and throat. Drink 1-2 glasses of water. Seek medical advice.

5. Fire fighting measures

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

None known

Special protection equipment for firefighters:

Wear self-contained breathing apparatus.

Wear protective equipment.

Special hazards by the product itself:

Non-combustible.

6. Accidental release measures

Personal precautions:

Avoid contact with skin and eyes.

Ensure adequate ventilation.

Environmental precautions:

Do not empty into drains / surface water / ground water.

Clean-up methods:

Remove mechanically.

Dispose of contaminated material as waste according to item 13.

7. Handling and storage

Handling:

Avoid skin and eye contact.

Keep container tightly sealed.

Storage:

Keep only in the original container.

Temperatures between + 5 $^{\circ}$ C and + 25 $^{\circ}$ C

Keep away from heat and direct sunlight.

Keep container tightly sealed.

Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

V001.0

MSDS-No.: 315307

8. Exposure controls / personal protection

Components with specific control parameters for workplace:

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m ³	Туре	Category	Remarks
1-METHOXYPROPANOL-2 107-98-2	100	375	Time Weighted Average (TWA).		ECTLV
1-METHOXYPROPANOL-2 107-98-2	150	568	Short Term Exposure Limit (STEL):		ECTLV
1-METHOXYPROPANOL-2 107-98-2			Skin designation.	Can be absorbed through the skin.	ECTLV
1-METHOXYPROPAN-2-OL 107-98-2	100	375	Time Weighted Average (TWA).		EH40 WEL
1-METHOXYPROPAN-2-OL 107-98-2	150	560	Short Term Exposure Limit (STEL):		EH40 WEL
1-METHOXYPROPAN-2-OL 107-98-2			Skin designation.	Can be absorbed through the skin.	EH40 WEL
1-METHOXYPROPAN-2-OL 107-98-2				Listed.	EH40 WEL

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Suitable breathing mask when there is inadequate ventilation.

Filter A2 is recommended in cases of prolonged exposure.

Hand protection:

For shorttime contact (e.g. as protection against splashes) protective gloves made from nitrile rubber (material thickness > 0.4 mm, break through time > 480 min) are recommended according to EN 374.

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

Eye protection:

Goggles which can be tightly sealed.

Skin protection:

Wear protective equipment.

General protection and hygiene measures:

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

9. Physical and chemical properties

General characteristics:

Appearance liquid viscous

White

Odor: typical

Phys./chem. properties:

Flash point $> 55 \,^{\circ}\text{C} (> 131 \,^{\circ}\text{F})$

MSDS-No.: 315307 V001.0

Solubility (qualitative)

miscible

(20 °C (68 °F); Solvent: Water)

10. Stability and reactivity

Conditions to avoid:

No decomposition if used according to specifications.

Materials to avoid:

None if used for intended purpose.

Hazardous decomposition products:

None known

11. Toxicological information

General toxicological information:

To the best of our knowledge no harmful effects are to be expected if the product is handled and used properly.

12. Ecological information

Persistence and degradability:

Ultimate biodegradation:

The product is not biodegradable.

General ecological information:

Do not empty into drains, soil or bodies of water.

13. Disposal considerations

Product disposal:

Waste incineration or treatment plant with the approval of the responsible local authority.

The valid EEC waste code numbers are not product-related but are largely source-related. The manufacturer is therefore unable to specify EEC waste codes for the articles or products used in the various sectors. These can be requested from the manufacturer.

Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

14. Transport information

Road transport ADR:

Not dangerous goods

Railroad transport RID:

Not dangerous goods

Inland water transport ADN:

Class: 9

Packaging group: Classification code: Hazard ident. number:

UN no.: 9003

Label:

Technical name: SUBSTANCES WITH A FLASH-POINT ABOVE 61 °C AND NOT

MORE THAN 100 °C

Marine transport IMDG:

Not dangerous goods

MSDS-No.: 315307 V001.0

Air transport IATA: Not dangerous goods

15. Regulations - classification and identification

Not subject of the identification regulations.

16. Other information

Further information:

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.