

Page 1 of 3

## FG3668-350A Wet n Black

Revision 0

Revision date

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name FG3668-350A Wet n Black

Company Turtle Wax Limited

East Gillibrands Skelmersdale Lancashire WN8 9TX England

MSDS@turtlewax.ltd.uk www.turtlewaxeurope.com

**Telephone** +44 (0)1695 722161 **Fax** +44 (0)1695 716621

**Emergency telephone** 

number

+44 (0)1695 722161 (Daytime)

Intended use Car Care Product.

### 2 HAZARDS IDENTIFICATION.

Main hazards Flammable

## 3. COMPOSITION / INFORMATION ON INGREDIENTS.

Hazardous ingredients

Mixed Hydrocarbon Isomers

 Conc.
 CAS
 EINECS
 Symbols/Risk phrases

 70 - 100%
 64742-48-9
 265-150-3
 Xn; R65 R10-66

### 4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.

Seek medical attention if irritation or symptoms persist.

**Eye contact** May cause irritation to eyes. Contact lenses should be removed. Rinse immediately with

plenty of water for 15 minutes holding the eyelids open. Seek medical attention if

irritation or symptoms persist.

**Inhalation** Considered to be not hazardous by inhalation.

Ingestion Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medical attention if

irritation or symptoms persist.

#### 5. FIRE FIGHTING MEASURES

**Extinguishing media** Use extinguishing media appropriate to the surrounding fire conditions.

**Fire hazards** carbon oxides may be formed in fire conditions.

**Protective equipment** Wear suitable respiratory equipment when necessary.

Print date 8-Feb-2008

Λ

# FG3668-350A Wet n Black

Revision
Revision date

**6. ACCIDENTAL RELEASE MEASURES** 

Personal precautions Ensure adequate ventilation of the working area. Surfaces contaminated with the

product will become slippery.

Environmental

Do not allow product to enter drains. Prevent further spillage if safe.

precautions
Clean up methods

Absorb with inert, absorbent material. Transfer to suitable, labelled containers for

disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation of the working area. Adopt best Manual Handling

considerations when handling, carrying and dispensing.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in

correctly labelled containers. Store at temperatures between 5 °C and 35 °C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**Engineering measures** Ensure adequate ventilation of the working area.

**Occupational exposure** 

Wash hands after handling the product.

controls

9. PHYSICAL AND CHEMICAL PROPERTIES

DescriptionLiquid.ColourClear.

Odour Characteristic.

Boiling point100°CFlash point42°CRelative density0.810

Viscosity Kinematic Viscosity in 10-6 m<sup>2</sup>/s at 40°C (ISO 3219) - 10

**Evaporation rate** <0.1 n-butyl acetate = 1.0

Melting point 0°C

10. STABILITY AND REACTIVITY

**Stability** Stable under normal conditions.

Conditions to avoid Do NOT allow to freeze. Store at temperatures below 35 °C.

Materials to avoid None.

Hazardous None.

decomposition products

11. TOXICOLOGICAL INFORMATION

**Toxicological information** No known adverse health effects.

12. ECOLOGICAL INFORMATION

**Ecotoxicity** No known adverse environmental effects.

Mobility Viscous liquid.

Degradability Readily biodegradable.

Bioaccumulation Does not bioaccumulate.

# FG3668-350A Wet n Black

Revision 0
Revision date

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations. Do not allow product to

enter drains.

**Disposal methods** Dispose of in compliance with all local and national regulations.

**Disposal of packaging** Empty containers can be sent for disposal or recycling.

14. TRANSPORT INFORMATION

ADR/RID Shipped in limited quantities under ADR.

UN 1263 Packing group III

Class 3 Hazard ID 30

Proper Shipping PAINT . Name

**IMDG** 

UN 1263 Packing group  $\parallel \parallel$  Class 3 Marine pollutant .

EmS Code F-E S-E

IATA

UN 1263 Packing group III
Class 3 Subsidiary risk Packing Instruction 310 Maximum quantity 220 L

(Cargo)

Packing Instruction 309 Maximum quantity 60 L

(Passenger)

#### 15. REGULATORY INFORMATION

Risk phrases R10 - Flammable.

Safety phrases S2 - Keep out of the reach of children.

 ${\sf S62}$  - If swallowed, do not induce vomiting: seek medical advice immediately and show

this container or label.

R10 - Flammable.

Further information Contains petroleum distillates.

Safety data sheet available for professional user on request.

#### **16. OTHER INFORMATION**

Text of risk phrases in

Section 3. R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

Print date 8-Feb-2008