



SAFETY DATA SHEET (Retail) Wheel Cleaner

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	(Retail) Wheel Cleaner
PRODUCT NO.	780
APPLICATION	Cleaner
SUPPLIER	Autosmart International Ltd Lynn Lane, Shenstone, nr Lichfield Staffordshire. WS14 0DH England www.autosmartinternational.com Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00) info@autosmartinternational.com
EMERGENCY TELEPHONE	Mob: +44 (0) 7808 971321 (24hrs) Tel: +44 (0) 1543 481616 (09:00 - 17:00) Fax: +44 (0) 1543 481549 (09:00 - 17:00)

2 HAZARDS IDENTIFICATION

Irritating to eyes and skin.

CLASSIFICATION Xi;R36/38.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content	Classification
2-BUTOXYETHANOL	203-905-0	111-76-2	1-5%	Xn;R20/21/22 Xi;R36/38
3-Lauramidopropyl trimethyl ammonium methyl sulfate	234-204-8	10595-49-0	< 1%	Xn;R22. Xi;R36. R43.
POTASSIUM HYDROXIDE	215-181-3	1310-58-3	< 1%	C;R35 Xn;R22

The Full Text for all R-Phrases are Displayed in Section 16

4 FIRST-AID MEASURES

INHALATION

Move the exposed person to fresh air at once. Rinse nose and mouth with water. Get medical attention if any discomfort continues.

INGESTION

Remove victim immediately from source of exposure. Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Rinse the skin immediately with lots of water. Use suitable lotion to moisturise skin. Get medical attention if irritation persists after washing.

EYE CONTACT

Promptly wash eyes with plenty of water while lifting the eye lids. Make sure to remove any contact lenses from the eyes before rinsing. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5 FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

SPECIFIC HAZARDS

Oxides of: Carbon. Nitrogen.

(Retail) Wheel Cleaner

6 ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS

For personal protection, see section 8.

ENVIRONMENTAL PRECAUTIONS

Do not discharge onto the ground or into water courses. To prevent release, place container with damaged side up.

SPILL CLEAN UP METHODS

Wear necessary protective equipment. Flush to sewer if local regulations permit. Stop leak if possible without risk. Wash thoroughly after dealing with a spillage. Absorb in vermiculite, dry sand or earth and place into containers. Containers with collected spillage must be properly labelled with correct contents and hazard symbol. Flush area clean with lots of water. Be aware of potential for surfaces to become slippery.

7 HANDLING AND STORAGE

USAGE PRECAUTIONS

Avoid spilling, skin and eye contact.

STORAGE PRECAUTIONS

Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

STORAGE CLASS

Chemical storage.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Name	Std	TWA - 8 hrs		STEL - 15 min		Notes
2-BUTOXYETHANOL	WEL	25 ppm		50 ppm		Sk
POTASSIUM HYDROXIDE	WEL				2 mg/m3	

WEL = Workplace Exposure Limit.
Sk = Can be absorbed through skin.

PROTECTIVE EQUIPMENT



PROCESS CONDITIONS

Provide eyewash station.

ENGINEERING MEASURES

No specific ventilation requirements noted, except this product must not be used in a confined space without good ventilation.

RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Workplace Exposure Limit.

HAND PROTECTION

Use protective gloves. The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material.

EYE PROTECTION

Wear splash-proof eye goggles to prevent any possibility of eye contact.

OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of skin contact. Provide eyewash station.

HYGIENE MEASURES

DO NOT SMOKE IN WORK AREA! Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes wet or contaminated. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE

Liquid

COLOUR

Light (or pale) Straw

(Retail) Wheel Cleaner

ODOUR	Mild (or faint).		
SOLUBILITY	Soluble in water Miscible with water.		
BOILING POINT (°C)	~ 100	MELTING POINT (°C)	~ 0
RELATIVE DENSITY	1.000 - 1.010 @ 20 °c	pH-VALUE, CONC. SOLUTION	13

10 STABILITY AND REACTIVITY**STABILITY**

Stable under normal temperature conditions and recommended use.

CONDITIONS TO AVOID

Avoid contact with acids. Reacts strongly with concentrated acids and chloro-hydrocarbons.

HAZARDOUS DECOMPOSITION PRODUCTS

No specific hazardous decomposition products noted.

11 TOXICOLOGICAL INFORMATION**INHALATION**

May cause irritation to the respiratory system.

INGESTION

Liquid irritates mucous membranes and may cause abdominal pain if swallowed.

SKIN CONTACT

Irritating to skin.

EYE CONTACT

Irritating to eyes.

HEALTH WARNINGS

SKIN CONTACT. Irritating to skin. EYE CONTACT. Irritating to eyes.

Prolonged or repeated exposure to vapour may cause: Coughing. Sore throat. Irritation of nose and throat.

ROUTE OF ENTRY

Ingestion.

MEDICAL SYMPTOMS

EYES AND MUCOUS MEMBRANES. Irritation of eyes and mucous membranes. SKIN. Skin irritation.

12 ECOLOGICAL INFORMATION**ECOTOXICITY**

No negative effects on the aquatic environment are known. The product is not expected to be hazardous to the environment. The product is not expected to be hazardous to waste water treatment processes. The product components are not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

WATER HAZARD CLASSIFICATION

WGK 0

13 DISPOSAL CONSIDERATIONS**GENERAL INFORMATION**

The packaging must be empty (drop-free, when inverted)

DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements. Recover and reclaim or recycle, if practical.

14 TRANSPORT INFORMATION

(Retail) Wheel Cleaner

UK ROAD CLASS	8		
PROPER SHIPPING NAME	CAUSTIC ALKALI LIQUID, N.O.S. (Sodium Nitrotriacetate, Potassium Hydroxide)		
UN NO. ROAD	1719	UK ROAD PACK GR.	III
ADR CLASS NO.	8	ADR CLASS	Class 8: Corrosive substances.
ADR PACK GROUP	III	HAZARD No. (ADR)	80
ADR LABEL NO.	8	HAZCHEM CODE	2R
CEPIC TEC(R) NO.	80GC5-II+III	RID CLASS NO.	8
RID PACK GROUP	III	UN NO. SEA	1719
IMDG CLASS	8	IMDG PAGE NO.	78 (vol 2)
IMDG PACK GR.	III	EMS	F-A, S-B
MFAG	See Guide	MARINE POLLUTANT	No.
UN NO. AIR	1719	AIR CLASS	8
AIR PACK GR.	III		

15 REGULATORY INFORMATION

LABELLING



Irritant

RISK PHRASES

R36/38 Irritating to eyes and skin.

SAFETY PHRASES

S2 Keep out of the reach of children

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S37 Wear suitable gloves.

S46 If swallowed, seek medical advice immediately and show this container or label.

S64 If swallowed, rinse mouth with water (only if the person is conscious).

P14 Contains 3-Lauramidopropyl trimethyl ammonium methyl sulfate. May produce an allergic reaction.

DETERGENT LABELLING

< 5% Non-ionic surfactants
Amphoteric surfactants
NTA (nitrilotriacetic acid) and salts thereof
Cationic surfactants

STATUTORY INSTRUMENTS

Chemicals (Hazard Information and Packaging) Regulations.

GUIDANCE NOTES

Workplace Exposure Limits EH40.

16 OTHER INFORMATION

GENERAL INFORMATION

Only trained personnel should use this material. This product has been manufactured under ISO 9001 and ISO 14001 Quality and Environmental Management Systems.

REVISION DATE 28/04/2009

REV. NO./REPL. SDS GENERATED 6

(Retail) Wheel Cleaner

RISK PHRASES IN FULL

R20/21/22	Harmful by inhalation, in contact with skin and if swallowed.
R22	Harmful if swallowed.
R35	Causes severe burns.
R36	Irritating to eyes.
R36/38	Irritating to eyes and skin.
R43	May cause sensitisation by skin contact.

DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.