Safety data sheet

Color Wood oil V

1. Identification of the substance/preparation and of the company/undertaking

Prepared on: 01-03-2011/ USAB Distributor:

Replaces: - DAY-system ab export (UK)

Grönkullen

Product use: Transparent oil for treatment of wood, exterior. SE-517 33 Bollebygd

Tel:+46 33-7002600 Fax:+46 33-7002610 Contact person:Environment department

Email: hse@day-system.com

2. Hazards identification

DSD/DPD-classification

The product shall not be classified as hazardous according to the national classification and labelling rules.

Additional information

Cloths with the product can self-ignite. Should be saturated with water or destroyed after use.

Allergy sufferers, please read information in section 11.

3. Composition/information on ingredients

Einecs no. CAS No. Substances DSD-Classification W/w%
Contains no substances subject to reporting requirements.

Please see section 16 for the full text of the R-phrases

4. First aid measures

Inhalation

Persons feeling indisposed must be placed in fresh air and kept under surveillance.

Ingestion

Drink a couple of glasses of water or milk.

Skin

Flush skin with large amounts of water and remove contaminated clothing, watches etc. simultaneously.

Eyes

Remove any contact lenses. Bend head backwards, open eye wide and flush with water for a few minutes or till discomfort has disappeared. Seek medical advice if discomfort continues.

Other information

When obtaining medical advice, show the safety data sheet or label. Symptoms: See section 11.

5. Fire-fighting measures

The product is not flammable. Extinguish with powder, foam, carbon dioxide or water mist.

6. Accidental release measures

Contain and absorb spill with sand or other absorbent material and transfer to suitable waste containers. See section 13 for instructions on disposal.

Avoid release of significant quantities of the product to water sources, sewers or the environment in general. If the product contaminates sea, lakes or drains, inform appropriate authorities in accordance with local regulations.

7. Handling and storage

Handling

Do not breathe vapour. Avoid contact with skin and eyes.

Storage

Keep container tightly closed, dry and out of reach of children. Away from food.

Prepared on: 01-03-2011/USAB Color Wood oil V

Replaces: -

8. Exposure controls/ personal protection

Precautions for use

Provide good airing. Running water and eye wash equipment should be available.

Dust, which is unhealthy, is produced when treated surfaces are grinded. Provide good ventilation. Use respiratory protection if necessary.

Respiratory protection

Not required.

Gloves and protective clothing

Use protective gloves of e.g. vinyl. Follow the glove supplier's instructions and information concerning use, break-through time etc.

Wear suitable protective clothing.

Eye protection

Wear eye protection if there is a possibility of direct contact or splashes.

Occupational exposure limits

Contains no substances subject to reporting requirements.

9. Physical and chemical properties

Appearance: Amber, transparent liquid Odour: Oily	Relative density (kg/l): 1,00 pH: 7.5
Solubility: Emulsifiable with water	Org. solvents (weight%): < 0,1
	Water (weight%): < 60

10. Stability and reactivity

Stable at normal handling. At high temperatures health-endanging decomposition products such as carbonmonooxide and carbondioxide may occur.

11. Toxicological information

Acute

Inhalation

Prolonged use in small, closed rooms may cause malaise.

Ingestion

Ingestion of large quantities may cause temporary malaise.

Skin contact

Prolonged or repeated contact may cause defatting, drying or irritant dermatitis.

Eye contact

Splashes in the eyes may cause irritation and smarting.

Risk of sensitization

Contains Isothiazolinone (CMIT/MIT, CAS-No. 55965-84-9) that may cause allergic reaction in contact with skin.

Long-term effects

12. Ecological information

The product is not classified as harmful to the environment according to the current legislation. The product should not be allowed to enter drains or watercourses.

Ecotoxicity

Ecotoxic information on the product itself does not exist.

13. Disposal considerations

The product is not dangerous waste. Should be disposed of in accordance with local regulations. Liquid residues of the product is classified as: EWC-code: 08 01 12 Waste paint and varnish other than those mentioned in 08 01 11.

Replaces: -

14. Transport information

The product is not covered by the rules for transport of dangerous goods by road and sea according to ADR and IMDG.

15. Regulatory information

Hazard designation: It has been assessed that the product shall not be classified as hazardous according to the national classification and labelling rules.

Other labelling

Cloths with the product can self-ignite. Should be saturated with water or destroyed after use.

VOC limit value (Cat. A/f): 130 g/l (2010)

Product VOC: max. 130 g/l

Chemical safety assessment

Chemical safety assessment has not been performed.

16. Other information

Restrictions on use

-

Training requirement

No special training is required, but a thorough knowledge of this safety data sheet should be a prerequisite condition.

Sources used

The supplier's safety data sheets and current legislation.

Other information

The safety data sheet is based on EU and national legislation. The user's working conditions are out of our control. The information should be considered as a description of the safety demands put on the product and not as a guarantee of the properties of the product.

Full text of the R-phrases that are stated in section 3.

No R-phrases.

(Made in Toxido®) UK