

# SAFETY DATA SHEET

## WINSOR & NEWTON LIQUIN ORIGINAL MEDIUM

According to Regulation (EC) No 1907/2006

### 1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME WINSOR & NEWTON LIQUIN ORIGINAL MEDIUM  
PRODUCT NO. 63106  
APPLICATION Medium for Oil Painting  
SUPPLIER ColArt International SA  
5 Rue Rene Panhard  
Z.I .Nord  
72021 Le Mans Cedex 2  
+33 2 43 83 83 00  
Lefranc-Bourgeois@colart.fr

### 2 HAZARDS IDENTIFICATION

Not regarded as a health or environmental hazard under current legislation.

CLASSIFICATION (1999/45) Not classified.

### 3 COMPOSITION/INFORMATION ON INGREDIENTS

Name	EC No.	CAS-No.	Content %	Classification (67/548/EEC)
Butanone oxime	202-496-6	96-29-7	< 1%	Xn;R21. Carc. Cat. 3;R40. Xi;R41. R43.
Hydrocarbons, C14-C18, <2% aromatics	927-632-8	64742-47-8	60-100%	Xn;R65. R66.

The Full Text for all R-Phrases is Displayed in Section 16

### 4 FIRST-AID MEASURES

#### INHALATION

Remove victim immediately from source of exposure. Provide rest, warmth and fresh air. Get medical attention if any discomfort continues.

#### INGESTION

DO NOT INDUCE VOMITING! Immediately rinse mouth and provide fresh air. Get medical attention.

#### SKIN CONTACT

Remove affected person from source of contamination. Remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.

#### EYE CONTACT

Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if any discomfort continues.

### 5 FIRE-FIGHTING MEASURES

#### EXTINGUISHING MEDIA

This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 6 ACCIDENTAL RELEASE MEASURES

#### SPILL CLEAN UP METHODS

Ventilate well. Wear necessary protective equipment. Absorb in vermiculite, dry sand or earth and place into containers.

### 7 HANDLING AND STORAGE

#### USAGE PRECAUTIONS

Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Persons susceptible to allergic reactions should not handle this product.

#### STORAGE PRECAUTIONS

Store in closed original container in a dry place. Store in a cool and well-ventilated place. Keep separate from food, feedstuffs, fertilisers and other sensitive material.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### PROTECTIVE EQUIPMENT

# WINSOR & NEWTON LIQUIN ORIGINAL MEDIUM



## ENGINEERING MEASURES

Provide adequate general and local exhaust ventilation.

## RESPIRATORY EQUIPMENT

No specific recommendation made, but respiratory protection must be used if the general level exceeds the recommended occupational exposure limit.

## HAND PROTECTION

Use suitable protective gloves if risk of skin contact.

## EYE PROTECTION

If risk of splashing, wear safety goggles or face shield.

## OTHER PROTECTION

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

## HYGIENE MEASURES

Wash at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Wash promptly with soap & water if skin becomes contaminated. When using do not eat, drink or smoke.

## 9 PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE	Liquid
COLOUR	Lightly coloured.
ODOUR	Hydrocarbon
BOILING POINT (°C)	150 - 200 760 mm Hg
MELTING POINT (°C)	< 0
RELATIVE DENSITY	0.89 20
VAPOUR PRESSURE	2 mm Hg 15
VOLATILE BY VOL. (%)	80
FLASH POINT (°C)	70 CC (Closed cup).
AUTO IGNITION	>250
TEMPERATURE (°C)	
FLAMMABILITY LIMIT - LOWER(%)	0.9
FLAMMABILITY LIMIT - UPPER(%)	6.0

## 10 STABILITY AND REACTIVITY

### STABILITY

Stable under normal temperature conditions.

### CONDITIONS TO AVOID

Avoid contact with acids and oxidising substances. Avoid excessive heat for prolonged periods of time.

### HAZARDOUS DECOMPOSITION PRODUCTS

High temperatures generate: Toxic gases/vapours/fumes of: Carbon dioxide (CO<sub>2</sub>). Carbon monoxide (CO).

## 11 TOXICOLOGICAL INFORMATION

### INHALATION

May cause sensitisation by inhalation.

### INGESTION

May cause discomfort if swallowed.

### SKIN CONTACT

May cause sensitisation by skin contact.

### EYE CONTACT

Spray and vapour in the eyes may cause irritation and smarting.

## 12 ECOLOGICAL INFORMATION

### ECOTOXICITY

Not regarded as dangerous for the environment.

## 13 DISPOSAL CONSIDERATIONS

# WINSOR & NEWTON LIQUIN ORIGINAL MEDIUM

## DISPOSAL METHODS

Dispose of waste and residues in accordance with local authority requirements.

### 14 TRANSPORT INFORMATION

ROAD TRANSPORT NOTES Not Classified

SEA TRANSPORT NOTES Not classified.

AIR TRANSPORT NOTES Not classified.

### 15 REGULATORY INFORMATION

#### RISK PHRASES

NC

Not classified.

#### SAFETY PHRASES

P14

Contains Butanone oxime. May produce an allergic reaction.

S2

Keep out of the reach of children.

#### EU DIRECTIVES

Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. System of specific information relating to Dangerous Preparations. 2001/58/EC.

### 16 OTHER INFORMATION

DATE 27/05/2011

#### RISK PHRASES IN FULL

R21 Harmful in contact with skin.

R65 Harmful: may cause lung damage if swallowed.

R40 Limited evidence of a carcinogenic effect.

R43 May cause sensitisation by skin contact.

R66 Repeated exposure may cause skin dryness or cracking.

R41 Risk of serious damage to eyes.

#### DISCLAIMER

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.