

SAFETY DATA SHEET

according to 1907/2006/EC, Article 31

Page 1 of 3

FG6216-367A Ice Synthetic Paste Wax

Revision 5 Revision date 18-05-2010

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY

Product name FG6216-367A Ice Synthetic Paste Wax

Company Turtle Wax Limited

East Gillibrands Skelmersdale Lancashire WN8 9TX England

MSDS@turtlewax.ltd.uk www.turtlewaxeurope.com

Telephone +44 (0)1695 722161 **Fax** +44 (0)1695 716621

Emergency telephone

number

+44 (0)1695 722161 (Daytime)

Intended use Car Care Product.

2. HAZARDS IDENTIFICATION

Main hazards Flammable

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous ingredients

	Conc.	CAS	EINECS	Symbols/Risk phrases
Mixed Hydrocarbon Isomers.	30-50%	64742-48-9	265-150-3	Xn; R65 R10-66
Straight run kerosine - kerosine (petroleum).	5-10%	8008-20-6	232-366-4	Xn; R65

4. FIRST AID MEASURES

Skin contact Wash off immediately with plenty of soap and water. Remove contaminated clothing.

Seek medical attention if irritation or symptoms persist.

Eye contact May cause irritation to eyes. Contact lenses should be removed. Rinse immediately

with plenty of water for 15 minutes holding the eyelids open. Seek medical attention if

irritation or symptoms persist.

Inhalation Considered to be not hazardous by inhalation.

Ingestion Rinse mouth thoroughly. DO NOT INDUCE VOMITING. Seek medical attention if

irritation or symptoms persist.

5. FIRE FIGHTING MEASURES

Extinguishing mediaUse extinguishing media appropriate to the surrounding fire conditions.

Fire hazards Carbon oxides may be formed in fire conditions.

Protective equipment Wear suitable respiratory equipment when necessary.

FG6216-367A Ice Synthetic Paste Wax

Revision Revision date 18-05-2010

6. ACCIDENTAL RELEASE MEASURES

Personal precautions Ensure adequate ventilation of the working area. Surfaces contaminated with the

product will become slippery.

Do not allow product to enter drains. Prevent further spillage if safe. **Environmental precautions**

Clean up methods Absorb with inert, absorbent material. Transfer to suitable, labelled containers for

disposal. Clean spillage area thoroughly with plenty of water.

7. HANDLING AND STORAGE

Handling Ensure adequate ventilation of the working area. Adopt best Manual Handling

considerations when handling, carrying and dispensing.

Storage Keep in a cool, dry, well ventilated area. Keep containers tightly closed. Store in

correctly labelled containers. Store at temperatures between 5 °C and 35 °C.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ensure adequate ventilation of the working area. **Engineering measures**

Occupational exposure

controls

Wash hands after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Description Paste. Colour Blue.

Odour Characteristic.

46°C Flash point Relative density 0.816

Viscosity 10-6 m²/s @ 40°C (ISO 3219) - , 400.

Evaporation rate <0.1 n-butyl acetate = 1.0

Melting point 76°C

10. STABILITY AND REACTIVITY

Stable under normal conditions. Stability

Conditions to avoid Do NOT allow to freeze. Store at temperatures below 35 °C.

Materials to avoid None. Hazardous decomposition None.

products

11. TOXICOLOGICAL INFORMATION

Toxicological information No known adverse health effects.

12. ECOLOGICAL INFORMATION

Ecotoxicity No known adverse environmental effects.

Mobility Viscous liquid.

Degradability Readily biodegradable. Bioaccumulation Does not bioaccumulate.

FG6216-367A Ice Synthetic Paste Wax

Revision 5 Revision date 18-05-2010

13. DISPOSAL CONSIDERATIONS

General information Dispose of in compliance with all local and national regulations. Do not allow product to

enter drains.

Disposal methods Dispose of in compliance with all local and national regulations.

Disposal of packaging Empty containers can be sent for disposal or recycling.

14. TRANSPORT INFORMATION

ADR/RID Shipped in limited quantities under ADR.

UN 1325 Packing group III
Class 4.1 Hazard ID 40

Proper Shipping FLAMMABLE SOLID, **Name** ORGANIC, N.O.S, .

IMDG

UN 1325 Packing group III
Class 4.1 Marine pollutant .

EmS Code F-A S-G

IATA

UN 1325 Packing group III
Class 4.1 Subsidiary risk -

Packing Instruction 420 Maximum quantity 100 kg

(Cargo)

Packing Instruction 419 Maximum quantity 25 kg

(Passenger)

15. REGULATORY INFORMATION

Labelling The product is classified in accordance with 67/548/EEC.

Risk phrases R10 - Flammable.

Safety phrases S2 - Keep out of the reach of children.

S46 - If swallowed, seek medical advice immediately and show this container or label.

Further information Contains petroleum distillates.

Safety data sheet available for professional user on request.

16. OTHER INFORMATION

Text of risk phrases in R10 - Flammable.

Section 3 R65 - Harmful: may cause lung damage if swallowed.

R66 - Repeated exposure may cause skin dryness or cracking.

Further information The information supplied in this Safety Data Sheet is designed only as guidance for the

safe use, storage and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication however no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other

process.

Revision This document differs from the previous version in the following areas: